



KunLun Two-Stroke Motorcycle Oils

【Introduction】

These series oils are formulated by blending certain amount of detergent dispersant, polyisobutylene and diluent with paraffinic base oil from Daqing Oil Field. They have good detergent property, lubricity, smoke emission and intersolubility, and meet the specification of FC series of Japan Automobile Standardization Organization (JASO). They reach the quality level of the same type oils of world famous companies.

【Performance】

- Excellent detergent & dispersing property: Can effectively reduce the generation of deposit on the cylinder wall and piston, avoid piston ring galling and keep the engine clean;
- Excellent antiwear performance: Can effectively reduce the wear of engine. Has excellent scuffing resistance property;
- Formula of low ash: super low smoke emission could keep the spark plug clean and prevent the preignition caused by deposit in ignition chamber.

【Application】

- FB series oils are applied to lubricating various air cooled two-stroke gasoline engines running under moderate working conditions with exhaust capacity less than 50ml, as well as small-type air cooled two-stroke engines of chain saw and lawn mower etc.
- FC series are suitable for lubrication of various air cooled two-stroke gasoline engines with exhaust capacity under 250mL (e.g. engines of Yamaha CY-80, Suzuki AX-100), as well as air cooled two-stroke engines of chain saw, lawn mower etc. They can also be used as the substitute of FB oils.

【Products】

FB and FC series two-stroke motorcycle oils.

【Package】

1L drum